


|                        |                                                                                                                                                                                                                                                                                                                                                                            |
|------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| article#               | <b>317-9v</b>                                                                                                                                                                                                                                                                                                                                                              |
| article description    | <b>CEE-flanged socket (70x70mm) 16A 7p 9h IP44/IP54</b>                                                                                                                                                                                                                                                                                                                    |
| description long       | CEE-flanged socket (70x70mm) 16A 7p 9h IP44/IP54<br>housing material: PA6<br>rated current: 16A<br>number of poles: 7 (6P+PE)<br>clock-position: 9h<br>rated voltage/frequency: 220-250V~ / 50+60Hz<br>contacts: brass nickel plated<br>connection technology: screw terminals<br>dimensions (flange/fixing center): 70x70 mm / 56x56 mm<br>IP protection class: IP44/IP54 |
| GTIN (EAN)             | 9003399045592                                                                                                                                                                                                                                                                                                                                                              |
| country of origin      | AT                                                                                                                                                                                                                                                                                                                                                                         |
| customs number         | 85366990                                                                                                                                                                                                                                                                                                                                                                   |
| net weight             | 0.180 kg                                                                                                                                                                                                                                                                                                                                                                   |
| packaging quantity     | 10                                                                                                                                                                                                                                                                                                                                                                         |
| minimum order quantity | 10                                                                                                                                                                                                                                                                                                                                                                         |

|                                 |                           |
|---------------------------------|---------------------------|
| ETIM 9.0                        | EC001317                  |
| IEC-ampereage                   | 16 A                      |
| Voltage according to EN 60309-2 | 200-250 V (50+60 Hz) blue |
| Number of poles                 | 7                         |
| Clock hour position             | 9 h                       |
| Identification colour           | Blue                      |
| Degree of protection (IP)       | IP54                      |
| Connection system               | Screwed terminal          |
| Angle of plug                   | Straight                  |
| Material                        | Plastic                   |
| Contact material                | CuZn                      |
| Surface treatment contacts      | Nickel-plated             |
| Flange size vertical            | 70 mm                     |
| Drill hole distance vertical    | 56 mm                     |
| Flange size horizontal          | 70 mm                     |
| Drill hole distance horizontal  | 56 mm                     |

|                        |                       |
|------------------------|-----------------------|
| a                      | 70 mm                 |
| b                      | 70 mm                 |
| c                      | 56 mm                 |
| d                      | 56 mm                 |
| e                      | 26 mm                 |
| f                      | 55 mm                 |
| g                      | 5,5 mm                |
| h                      | 52 mm                 |
| i                      | 107 mm                |
| j                      | 107 mm                |
| wire flexible          | 1-2,5 mm <sup>2</sup> |
| wire solid             | 1-4 mm <sup>2</sup>   |
| contact screws         | 100 Ncm               |
| dismantling length     | 50 mm                 |
| stripping length       | 10-12 mm              |
| ambient temperature    | -25 – 40 °C           |
| temperature resistance | -25 – 80 °C           |
| IK-code *)             | IK08                  |



\*) The IK-test is not part of the IEC 60309 standard for industrial plugs and socket-outlets or the IEC 60884 standard for household plugs and socket-outlets. PC Electric GmbH has therefore tested the IK-codes of these products in accordance with IEC 62262 and according to the test method of IEC 60068-2-75 Ehc, with conditioning for 48 hours at 40°C and a relative humidity of 95%.



<https://www.pcelectric.at/shop/en/?func=detail&artnr=317-9v>